

CAT 7

S/FTP 4 PR AWG 23/1



CONDUCTOR	Solid copper conductor 23 AWG/1
INSULATION	Foam PE
PAIR SHIELDING	Aluminium foil
SHIELDING	Tinned copper wire braid
SHEATH	LSZH
REFERENCE STANDARD	IEC 61156-5 & ISO/IEC 11801

PHYSICAL PROPERTIES:

BENDING RADIUS (Installation)	8 x Ø
MAX. RECOMMENDED PULLING TENSION	80 N
NOMINAL OUTER Ø	7.7 ± 0.3 mm
CABLE WEIGHT	66 kg/km
CORE IDENTIFICATION Pair colours	<ol style="list-style-type: none"> 1. White/Blue stripe & Blue 2. White/Orange stripe & Orange 3. White/Green stripe & Green 4. White/Brown stripe & Brown
PACKAGING	500 m drum, 1000 m drum

MAIN CHARACTERISTICS:

FIRE PERFORMANCE	Dca-s1a, d2, a1 IEC 60332-1-2 IEC 60332-3-22
MAX. CONDUCTOR DC RESISTANCE	95 Ω/km @20 °C
CONDUCTOR LOOP RESISTANCE	max. 19 Ω/100 m @20 °C
NOM. MUTUAL CAPACITANCE	≤ 5.6 nF/100 m @1 kHz
CAPACITANCE UNBALANCE PAIR TO GROUND	≤ 1600 pF/km @1 kHz
MIN. INSULATION RESISTANCE	5000 MΩ/m
IMPEDANCE	100 ± 25 Ω @100 MHz
RATED TEMPERATURE	75 °C
OPERATING TEMPERATURE RANGE	-20 °C - 75 °C

Part number	Cable type	Colour	Standard length m
3340124042	CAT 7 S/FTP AWG 23/1	Black	500 m
3340224042	CAT 7 S/FTP AWG 23/1	Yellow	500 m
3340324042	CAT 7 S/FTP AWG 23/1	Grey	500 m
3340424042	CAT 7 S/FTP AWG 23/1	White	500 m
3340524042	CAT 7 S/FTP AWG 23/1	Orange	500 m
3340624042	CAT 7 S/FTP AWG 23/1	Blue	500 m
3340724042	CAT 7 S/FTP AWG 23/1	Red	500 m
3340824042	CAT 7 S/FTP AWG 23/1	Green	500 m
3341124042	CAT 7 S/FTP AWG 23/1	Black	1000 m
3341224042	CAT 7 S/FTP AWG 23/1	Yellow	1000 m
3341324042	CAT 7 S/FTP AWG 23/1	Grey	1000 m
3341424042	CAT 7 S/FTP AWG 23/1	White	1000 m
3341524042	CAT 7 S/FTP AWG 23/1	Orange	1000 m
3341624042	CAT 7 S/FTP AWG 23/1	Blue	1000 m
3341724042	CAT 7 S/FTP AWG 23/1	Red	1000 m
3341824042	CAT 7 S/FTP AWG 23/1	Green	1000 m

PERFORMANCE:

F (MHz)	ATT (dB/100 m)	RL (dB)	NEXT (dB)	PS NEXT (dB)	ACRF (EL FEXT) (dB/100 m)	PS ACRF (PS EL FEXT) (dB/100 m)	PD (ns/100 m)
4.0	3.6	30	98	95	96	92	449
8.0	5.0	32	98	95	94	89	444
10.0	5.6	35	98	95	91	90	442
16.0	7.2	35	98	95	81	76	440
20.0	8.1	38	99	96	81	77	439
25.0	9.1	39	98	95	84	76	438
31.2	10.0	39	97	94	83	77	437
62.5	14.5	34	95	92	79	76	436
100.0	17.7	32	92	89	82	73	435
200.0	26.1	30	88	85	69	66	434
250.0	27.9	28	86	83	74	65	434
300.0	31.9	27	86	83	69	64	433
400.0	37.8	28	83	80	59	56	433
500.0	40.7	23	81	78	56	51	433
600.0	45.8	25	80	77	58	52	433

F = Frequency

ATT = Attenuation

RL = Return Loss

NEXT = Near End Crosstalk

PS NEXT = Power Sum Near End Crosstalk

ACRF (EL FEXT) = Attenuation to Crosstalk Ratio Far End Crosstalk

PS ACRF (PS EL FEXT) = Power Sum Attenuation to Crosstalk Ratio Far End Crosstalk

PD = Phase Delay